



# IN-LINE BOTTLE JACKS

- Heat-treated extension screw allows low pick-up height adjustment and maximum lift height
- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912
- Unique cross-type forged release valve assures positive control
- A wide, rugged base provides stability and strength
- In-line pump allows for easy jack positioning under load

10128  
12 Ton Capacity



10120  
12 Ton Capacity



10208  
20 Ton Capacity

10200  
20 Ton Capacity



| Model | Capacity | Minimum Height | Maximum Height | Hydraulic Lifting | Extension Screw | Base Size Length | Base Size Width | G.W.    |
|-------|----------|----------------|----------------|-------------------|-----------------|------------------|-----------------|---------|
| 10120 | 12 Ton   | 9-1/2"         | 18-5/8"        | 6"                | 3-1/8"          | 7"               | 4-1/4"          | 19 Lbs. |
| 10128 |          | 6"             | 10-3/4"        | 3-1/8"            | 1-5/8"          |                  |                 | 16 Lbs. |
| 10200 | 20 Ton   | 9-1/2"         | 18-5/8"        | 6"                | 3-1/8"          | 7-3/4"           | 5"              | 28 Lbs. |
| 10208 |          | 6-1/2"         | 11-1/4"        | 3-1/8"            | 1-5/8"          |                  |                 | 23 Lbs. |

# SIDE PUMP BOTTLE JACKS



- Hydraulic system is protected from internal damage by a by-pass mechanism U.S. Patent No.5,946,912
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- Unique cross-type forged release valve assures positive load control
- A wide, rugged base provides stability and strength

| Model  | Capacity | Minimum Height | Maximum Height | Hydraulic Lifting | Extension Screw | Base Size Length | Base Size Width | G.W.     |
|--------|----------|----------------|----------------|-------------------|-----------------|------------------|-----------------|----------|
| 10025C | 2 Ton    | 7-1/4"         | 13-5/8"        | 4-3/8"            | 2"              | 3-3/4"           | 3-5/8"          | 7 Lbs.   |
| 10045C | 4 Ton    | 8"             | 15-3/8"        | 5"                | 2-3/8"          | 4"               | 3-7/8"          | 9 Lbs.   |
| 10065C | 6 Ton    | 8-5/8"         | 16-3/4"        | 5-1/8"            | 3"              | 4-1/4"           | 4"              | 12 Lbs.  |
| 10085C | 8 Ton    | 8-7/8"         | 17-5/8"        | 6"                | 2-3/4"          | 4-3/4"           | 4-3/4"          | 14 Lbs.  |
| 10125C | 12 Ton   | 9-1/2"         | 18-5/8"        | 6"                | 3-1/8"          | 5-1/4"           | 5-1/8"          | 18 Lbs.  |
| 10129C |          | 6"             | 10-5/8"        | 3"                | 1-5/8"          |                  |                 | 14 Lbs.  |
| 10205C | 20 Ton   | 9-1/2"         | 18-5/8"        | 6"                | 3-1/8"          | 6-1/4"           | 5-7/8"          | 27 Lbs.  |
| 10209C |          | 6-1/2"         | 11-1/4"        | 3-1/8"            | 1-5/8"          |                  |                 | 21 Lbs.  |
| 10300  | 30 Ton   | 11"            | 18"            | 7"                | N/A             | 8-1/8"           | 6-7/8"          | 55 Lbs.  |
| 10500  | 50 Ton   | 9-1/2"         | 13-7/8"        | 4-3/8"            |                 | 10-7/8"          | 7-5/8"          | 107 Lbs. |